



Geberit Kombifix element for wall-hung WC, H109, with Delta cistern 12 cm (UP182)

Application purpose

- For wall-hung WC with fastening distance 18 cm or 23 cm
- For installation in front of or inside a solid wall
- Not suitable for installation in a drywall

Characteristics

- Installation height 109.5 cm
- Push-in fastening for outlet bend
- Installation depth 12 cm
- Supporting frame galvanized
- Concealed cistern fully insulated against condensation
- Dual flush with Delta50 or Delta21 actuator plate
- Stop-and-go flush or single flush with Delta15, Delta40 or Delta11 actuator plate
- Small flush volume can be set
- Large flush volume can be set
- Water supply connection at centre back or at the top

Technical data

Flush volume factory setting	6 and 3 l
Flush range small	3 / 4 l
Flush range large	6 / 9 l
Interruptible stop-and-go flush	6 / 9 l

Scope of delivery

- Mounting frame with 4 fastening brackets
 - 2 threaded rods M12 for ceramics fastening
 - Protection cover for service opening, polystyrene foam
 - Angle stop valve R 1/2, with adapter ring
 - Outlet bend bracket
 - Connector set dia. 90 mm
 - WC outlet bend, HDPE, dia. 90/90 mm
 - Adapter sleeve, dia. 90/110 mm
 - Two protection plugs
 - Fastening material
- Excluded:
- Actuator plate

Article

Article no.	Description
110.171.00.1	Geberit Kombifix element for wall -hung WC, H109, with Delta cistern 12 cm (UP182)