



Geberit Duofix element for wall-hung WC, H112, with Sigma cistern 8 cm (UP720)

Application purpose

- For installation in front of a solid or drywall
- For installation in drywall or prewall construction covered with panels (gypsum or wood)
- For installation in room-height prewall or partition wall
- For wall-hung WC with fastening distance 18 cm or 23 cm

Characteristics

- Element height 112 cm
- Element depth 8 cm
- Dual flush with Sigma01, Sigma20, Sigma50, Sigma60, Sigma80, Bolero actuator plate
- Stop-and-go flush with Sigma10, Mambo or Tango actuator plate
- Adjustable flushing volume
- M12 fastening for ceramic appliances, fastening distance 18 cm or 23 cm
- Concealed cistern fully insulated against condensation
- Water supply connection at the top, offset to the left side
- Fastening for outlet bend adjustable in depth and sound-absorbing
- Powder-coated frame, ultramarine blue
- Feet galvanized, adjustable 0 - 12 cm
- Self-locking feet for tool-free alignment of the element
- Self-supporting

Technical data

Flush volume factory setting	6 and 3 l
Flush volume small	3 l
Flush range large	6 / 9 l
Interruptible stop-and-go flush	6 / 9 l

Scope of delivery

- Water supply connection R 1/2" with integrated angle stop valve and hand wheel
 - Two protection plugs
 - Protection cover for service opening, can be cut to length
 - Flush bend
 - 2 threaded rods M12 for ceramics fastening
 - WC connection set, dia. 90 mm
 - WC outlet bend, HDPE, dia. 90 mm, extended
 - Adapter sleeve, dia. 90/110 mm
 - Geberit AquaClean conduit pipe
 - 2 wall anchorings
 - Fastening material
- Excluded:
- Actuator plate

Article

Article no.	Description
111.726.00.1	Geberit Duofix element for wall -hung WC, H112, with Sigma cistern 8 cm (UP720)