



Geberit Duofix element for wall-hung WC, H112, with Sigma cistern 12 cm (UP320), connection for odour extraction with filtration



Application purpose

- For a floor construction of 0 - 20 cm
- For installation in front of a solid or drywall
- For installation in drywall or prewall construction covered with panels (gypsum or wood)
- For installation in room-height prewall or partition wall
- For wall-hung WC with fastening distance 18 cm or 23 cm
- For connecting the actuator plate Sigma40 with the odour extraction unit

Characteristics

- Dual flush with actuator plate Sigma40
- Concealed cistern for tool-free mounting and repair work
- Tool-free fastening for outlet bend, sound-absorbing, adjustable in depth with 8 positions, adjustable range 45 mm
- Self-locking feet for tool-free alignment of the element
- Feet galvanized, infinitely adjustable 0 - 20 cm
- Self-supporting
- Powder-coated frame, ultramarine blue
- Rotating foot plate, for installation in UW 50 and UW 75 U wall profiles
- Water supply connection at the top, offset to the left side
- Outlet mounting box, can be universally positioned

Technical data

Flush volume factory setting	6 and 3 l
Flush range large	4.5 / 6 / 7.5 l
Flush range small	3-4 l

Scope of delivery

- Water supply connection R 1/2" with integrated angle stop valve and hand wheel
- Geberit AquaClean conduit pipe
- Protection plug
- Protection cover for service opening, can be cut to length
- 2 threaded rods M12 for ceramics fastening
- WC connection set, dia. 90 mm
- WC outlet bend, HDPE, dia. 90 mm
- Adapter sleeve, dia. 90/110 mm
- Fastening material
- Flush pipe with odour extraction adapter
- Outlet mounting box

Excluded:

- Actuator plate

Article

Article no.	Description
111.370.00.5	Geberit Duofix element for wall-hung WC, H112, with Sigma cistern 12 cm (UP320), connection for odour extraction with filtration