




**Geberit AquaClean 8000plus, complete solution, wall-hung**


---


**Application purpose**

- For convenient and odourless toilet use
- For gentle cleaning of the anal and vaginal areas with water

**Characteristics**

- Surface-coated ceramic appliance
- WC seat and lid with lowering function
- Infrared user detection
- Odour extraction unit with active carbon filter can be activated
- Spray arm with extendable nozzles for anal and vaginal area
- Spray arm position can be set to 7 positions
- Oscillating spray (automatic forward and reverse motion of the spray arm can be adjusted)
- Pulsating massage spray can be connected
- Spray intensity adjustable in 7 levels
- Automatic pre-rinsing of spray nozzle with fresh water and post-rinsing with Geberit nozzle cleaner
- Integrated hot water tank
- Adjustable storage water heater operating mode (ON/OFF/economy mode)
- Temperature of shower water can be adjusted
- Shower spray gradually cools down continuously during shower procedure
- Warm air dryer can be added
- Dryer arm can be extended
- Temperature of warm air dryer can be adjusted
- 4 user profiles can be programmed
- Water supply connection on the left side
- Functions and settings via remote control

## Technical data

Load WC seat / WC lid max.	150 kg
Air volume flow rate dryer	12 m <sup>3</sup> /h
Flow rate anal shower	2.1 - 5.5 l/min
Flow rate Lady shower	1.4 - 3 l/min
Spray time factory setting	20 s
Number of shower pressure settings	7
Storage water heater capacity	2.0 l
Length of mains connection cable	70 cm
Mains frequency	50 - 60 Hz
Power consumption	1000 W
Power consumption economy mode / with heating element switched on	1 / 9 W
Protection class	I
Protection degree	IPx4
Nominal voltage	230 V AC
Air volume flow rate odour extraction unit	10 m <sup>3</sup> /h
Flow pressure range	1 - 10 bar
Dryer temperature factory setting	45 °C
Dryer temperature range	20 - 45 °C
Operating temperature	10 - 40 °C
Storage temperature	-10 - +60 °C
Water temperature factory setting	37 °C
Water temperature range	10 - 39 °C

## Scope of delivery

- Remote control with LC display, wall bracket and batteries, LR03 (AAA)
- Cover plate for remote control compartment
- Active carbon filter
- Geberit nozzle cleaner
- Water supply connection set for UP300 / UP320 concealed cistern
- Dryer fan with housing
- Acoustical insulation set
- Fastening material
- Spray shield

## Article

Article no.	Colour
<b>180.100.11.2</b>	white alpine

- Using the supplied standard connecting material, all concealed cisterns (except for UP200) can be connected with the prepared conduit pipe.
- The UP200 concealed cistern additionally requires the reinforced braided hose with T-piece (art. no. 240.839.00.1) to be ordered.