


**Geberit lavatory tap type 185, mains operation, with mixer and handle**

**Application purpose**

- For cold and hot water connection
- For extracting tap water
- For the public and semi-public domain
- For installation in washbasin or counter top

**Characteristics**

- Temperature adjustment via the mixer lever
- Not possible to set just hot water and just cold water
- Proportion of hot water can be limited
- Infrared user detection
- Automatic triggering
- Self-calibrating infrared control
- Vandal-resistant
- Functions can be adjusted and queried with Geberit Service Handy
- Flush actuator can be deactivated by Geberit Clean Handy
- Volume flow control with aerator
- Water saving mode can be set
- Hygienic flush adjustable
- Integrated check valve
- Electrical power supply via power supply unit

**Technical data**

Differentiated pressure CW/WW	≤ 1.5 bar
Product material	Chrome-plated brass
Activation distance factory setting	16 - 18 cm
Activation distance adjustment range	1 - 33 cm
Ambient temperature	1 - 40 °C
Operating pressure	0.5 - 8 bar
Maximum operating temperature water, short-term	90 °C
Flow rate at 3 bar	6 l/min
Mains frequency	50 Hz
Nominal voltage	230 V AC
Operating voltage	12 V AC
Operating temperature water max.	65 °C

**Scope of delivery**

- 2 metal-reinforced hoses R 3/8"
- 2 basket filters
- Key for aerator
- 1.5 m connection cable
- Power supply unit
- Fastening material

## Article

Article no.	Colour
116.155.21.1	bright chrome-plated