


Geberit lavatory tap type 185, battery operation, with mixer and handle

Application purpose

- For cold and hot water connection
- For extracting tap water
- For the public and semi-public domain
- For installation in washbasin or counter top

Characteristics

- Temperature adjustment via the mixer lever
- Not possible to set just hot water and just cold water
- Proportion of hot water can be limited
- Infrared user detection
- Automatic triggering
- Self-calibrating infrared control
- Vandal-resistant
- Functions can be adjusted and queried with Geberit Service Handy
- Flush actuator can be deactivated by Geberit Clean Handy
- Volume flow control with aerator
- Water saving mode can be set
- Hygienic flush adjustable
- Integrated check valve
- Electrical power supply from battery
- Battery is sufficient to activate the water flow 200,000 times
- Warning if the battery is low
- Energy saving mode can be set

Technical data

Differentiated pressure CW/WW	≤ 1.5 bar
Product material	Chrome-plated brass
Activation distance factory setting	16 - 18 cm
Activation distance adjustment range	1 - 33 cm
Ambient temperature	1 - 40 °C
Operating pressure	0.5 - 8 bar
Maximum operating temperature water, short-term	90 °C
Flow rate at 3 bar	6 l/min
Operating voltage	6 V DC
Battery type	CR - P2 (6 V)
Operating temperature water max.	65 °C

Scope of delivery

- 2 metal-reinforced hoses R 3/8"
- 2 basket filters
- 6 V battery
- Key for aerator
- Fastening material

Article

Article no.	Colour
116.255.21.1	bright chrome-plated