

## TEMPOMATIC 4 wall-mounted :

### SPECIFICATIONS

Electronic wall mounted washbasin tap, L.110mm, with 6V Lithium battery-operated, electronic control unit and solenoid valves integrated in the body of the tap. Flow rate set at 3 litres/min. with adjustable flow straitener and anti-blocking security. Maintenance cover secured by hidden screws. Brand DELABIE type TEMPOMATIC 4 wall-mounted with integrated batteries. Ref. 443406 (or approved equivalent)

Réf. : 443406 : wall mounted L.125

Réf. : 443426 : L. 125&nbsp;for panels 1-22mm

Réf. : 443506 : wall mounted L.190

Réf. : 443526 : L. 190 for panels 1-22mm

- » • 6V Lithium battery type 223 supplied.
- We recommend installing a PREMIX Compact pre-mixer to supply pre-mixed water to the tap (see below).
- 45 sec. duty flush every 24h after the last use to prevent the proliferation of bacteria.



### FONCTIONING AND APPLICATION

#### Function:

- Automatic opening/closing by presenting/removing hands from sensor detection range.
- Duty flush to prevent proliferation of bacteria (45 seconds flush every 24 hours after the last use).

Use: All public and commercial places, medical sector, food industry, care homes for the less able, offices, restaurants etc.

### PRODUCT ADVANTAGES

- UNRESTRICTED INSTALLATION on any isolated basin (no additional power supply required) due to integrated battery. Simply connect the flexibles, no specific adjustment required.
- INFRARED SENSOR at the end of the spout optimises detection of hands.
- ADJUSTABLE FLOW STRAITENER: (Delabie patented) pre-set at 3 litres/min. at 3 bar and adjustable from 1 to 6 litres/min. using an Allen key directly on the flow-straitener.
- WATER SAVING: approx. 90% compared to classical taps due to lower flow rate and shorter flow duration.
- TOTAL HYGIENE: no manual contact, avoiding the development of bacteria/germs carried by the hands.
- EASY MAINTENANCE: independent modules are accessible via the front cover. Average life of 6V batteries is 3-6 years, with integrated battery power check.
- ANTI-BLOCKING SAFETY: avoids risk of continuous flow (automatic closure after 30 sec.s of

continuous detection in case of abuse, re-opening as soon as hands are presented again).

- RELIABILITY: corrosion-proof solenoid valve. Reliable presence detection.
- 3 YEAR WARRANTY.

443406

