



Commercial & public fittings > Basin fittings > Electronic tap > TABLE MOUNTED

TEMPOMATIC 2 :

SPECIFICATIONS

Electronic basin tap with power supply 230-12V with transformer (separate electronic control box IP65). Infrared detection of presence. Regulated flow rate 8l./min. with scale proof aerator and anti-blocking in flow safety device. Programmed Periodic Rinsing during 45 sec. every 24h after the last use, to prevent risks of legionella infection. Reinforced fixing by 2 stainless steel rods and lock-nuts. Brand DELABIE type TEMPOMATIC 2 Power supply 230-12V with transformer. Ref. 444000

x Réf. : 444000 : mains supply 230/12V

- » • Programmed Periodic Rinsing during 45 sec. every 24h after the last use, to prevent risks of legionella infection.
- We recommend to provide a PREMIX compact thermostat for mixed water to be installed under the washbasin (see below).



FONCTIONING AND APPLICATION

- Automatic opening/closing by presenting/removing hands from sensor detection range.
- Programmed Periodic Rinsing during 45 sec. every 24h after the last use, to prevent risks of legionella infection.
- Use: all public and commercial places, medical sector and food industry, disabled person sanitariums, offices, restaurants...

PRODUCT ADVANTAGES

- AESTHETIC: fluid, timeless and high-tech.
- VANDAL-PROOF: reinforced fixing and shock-proof detection cell.
- FULL HYGIENE without manual contact, avoiding the propagation of bacteria/germs carried by the hands.
- WATER SAVING: about 80% in comparison to classical taps (due to shorter flow rate and flow duration).
- ANTI-BLOCKING SAFETY: avoids risk of continuous flow (automatic closing after 60 sec. of continuous detection in case of malevolence, automatic reset).
- EASY MAINTENANCE: independent separately accessible units and auto-diagnostic leds.
- RELIABILITY: corrosion-proof solenoid valve. Foolproof detection of presence.
- SCALE PROOF AERATOR: 10 times slower scale deposit than a standard aerator.
- 3 YEARS WARRANTY.

444000

