



Geberit Duofix element for wall-hung WC, H112, with Delta cistern 12 cm (UP182)

Application purpose

- For front actuation
- For installation in part-height or room-height drywall construction in front of a solid or drywall construction
- For wall-hung WC with fastening distance 18 cm or 23 cm
- For a floor construction of 0 - 20 cm

Characteristics

- Installation depth 12 cm
- Self-supporting
- Feet galvanized, infinitely adjustable 0 - 20 cm
- Powder-coated frame, ultramarine blue
- Dual flush with Delta50 or Delta21 actuator plate
- Stop-and-go flush or single flush with Delta15, Delta40 or Delta11 actuator plate
- Concealed cistern fully insulated against condensation
- Immediate post flush possible with factory setting
- Frame with dia. 9 mm drilling holes for fastening in wood frame construction
- Foot plate plastic, depth suitable for mounting in UW50 profiles
- Adjustable flushing volume
- Water supply connection at centre back or at the top

Technical data

Flush volume factory setting	6 and 3 l
Flush range small	3 / 4 l
Flush range large	6 / 9 l
Interruptible stop-and-go flush	6 / 9 l

Scope of delivery

- Galvanized leg supports, adjustable, premounted
- 2 threaded rods M12 for ceramics fastening
- Protection cover for service opening, polystyrene foam
- Angle stop valve R 1/2" with adapter ring
- Outlet bend bracket
- Connector set dia. 90 mm
- WC outlet bend, HDPE, dia. 90/90 mm
- Adapter sleeve, dia. 90/110 mm
- Two protection plugs
- Fastening material

Excluded:

- Actuator plate

Article

Article no.	Description
458.160.00.1	Geberit Duofix element for wall -hung WC, H112, with Delta cistern 12 cm (UP182)